

Technical Data Sheet



Polypropylene Fibers MIF02

Description

FIBEREGO MIF02 helps the surface be smooth and flawless. It is a synthetic fiber that spun from isotactic polypropylene polymerized by propylene, non-toxic and easy to disperse in water.

Specifications and characteristics	
Material	100% virgin monofilament polypropylene
Color	Bright white
Specific Gravity	0.91
Typical Dosage Rates	0.5-0.8 KG/MT
Diameter	30µm
Length	0.118" (3mm)
Melt Point	160°C
Ignition Point	590°C
Electrical/Thermal Conductivity	Low
Water Absorption	<2%
Acid and Alkali Resistance	>95%
Tensile Strength	600 M Pa

Application

Wall putty (Skim coat)

Advantage

- Light weight
- High strength
- Good elasticity
- Excellent abrasion resistance
- Corrosion resistance
- Aging resistance

Packaging

- Customized packaging, including:
- Water-soluble film bag
- Water soluble paper bag
- Plastic bag
- plastic bucket

Dosage

The standard dosage rate is 0.5KG/MT. FIBEREGO MIF02 should be added per project specifications or engineer's instructions.

Shelf Life & Storage

2 years in original, unopened package. Store in cool and dry conditions

This information is based on our present state of knowledge and is intended to provide general notes about our products and their use only. It should not therefore be construed as guaranteeing the consistence or permanency of the products or specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.